

# Conquest 8x8 XT



## ENGINE

DISPLACEMENT	747cc
TYPE	4-cycle OHV
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Liquid
ALTERNATOR	60 AMP
HP	30

## STEERING/WHEELS/TIRES

STEERING	Multi Position, one piece handlebar
RIMS	Steel off-set
TIRES	ARGO AT189 25 X 12-9
GROUND PRESSURE	2.5 psi (17.2 kPa)
GROUND CLEARANCE - TIRES	9 in (230 mm)
GROUND CLEARANCE - TRACKS	10 in (255 mm)
CONTROLS	Right hand twist grip throttle

## POWERTRAIN

TRANSMISSION	Admiral
TRANSMISSION OPTION	STD
FINAL DRIVE	RC60 chains
DRIVE BELT	HD
GEAR SELECTION	L/H/N/R
CLUTCH	Belt-driven
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	OPT

## DIMENSIONS/WEIGHT/CAPACITY

LENGTH	132 in (3360 mm)
WIDTH	65 in (1651 mm)
HEIGHT	79 in (2007 mm)
LOAD CAPACITY - LAND	1,360 lb. (617 kg)
LOAD CAPACITY - WATER	860 lb. (390 kg)

## DIMENSIONS/WEIGHT/CAPACITY - continued

LOAD CAPACITY - REAR	NA
TOWING CAPACITY	2,000 lb. (907 kg)
DRY WEIGHT	2,195 lb. (996 kg)
FUEL CAPACITY	7.1 gal (27 ltr)
SEAT CAPACITY	2Land / NA
FRONT RACK	NO
SPEED ON LAND	17 mph (27 km)
SPEED ON WATER	3 mph (5 km)

## FEATURES

BRUSHGUARD	OPT
WINCH	OPT
SKID PLATE	YES
BILGE PUMP	YES
AXLE BEARING EXTENSIONS	Standard
ENTRY STEP	OPT
SEATING TYPE	Standard
BEDLINER	NO
OPERATING CONDITIONS	-40°C - +40°C

## INSTRUMENTATION

Analog Digital Gauge Cluster, Speedometer, Odometer, Voltmeter, Hour Meter, Tachometer, Low Oil Pressure, Parking Brake Reminder Lights and Check Engine Light

## COLORS

AVAILABLE COLORS	Industrial Yellow
------------------	-------------------

\*OPT are Dealer Installed items



## Conquest 8x8 XT-x

### ENGINE

DISPLACEMENT	747cc
TYPE	4-cycle OHV
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Liquid
ALTERNATOR	60 AMP
HP	30

### STEERING/WHEELS/TIRES

STEERING	Multi Position, one piece handlebar
RIMS	Steel off-set
TIRES	ARGO AT189 25 X 12-9
GROUND PRESSURE	2.5 psi (17.2 kPa)
GROUND CLEARANCE - TIRES	9 in (230 mm)
GROUND CLEARANCE - TRACKS	10 in (255 mm)
CONTROLS	Right hand twist grip throttle

### POWERTRAIN

TRANSMISSION	Admiral
TRANSMISSION OPTION	STD
FINAL DRIVE	RC60 chains
DRIVE BELT	Standard
GEAR SELECTION	L/H/N/R
CLUTCH	Belt-driven
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	OPT

### DIMENSIONS/WEIGHT/CAPACITY

LENGTH	132 in (3360 mm)
WIDTH	65 in (1651 mm)
HEIGHT	79 in (2007 mm)
LOAD CAPACITY - LAND	1055 lb. (479 kg)
LOAD CAPACITY - WATER	NA

### DIMENSIONS/WEIGHT/CAPACITY - continued

LOAD CAPACITY - REAR	NA
TOWING CAPACITY	2,000 lb. (907 kg)
DRY WEIGHT	2,045 lb. (928 kg)
FUEL CAPACITY	7.1 gal (27 ltr)
SEAT CAPACITY	2 Land / NA
FRONT RACK	NO
SPEED ON LAND	17 mph (27 km)
SPEED ON WATER	3 mph (5 km)

### FEATURES

BRUSHGUARD	YES
WINCH	4,500 lb. ProVantage
SKID PLATE	YES
BILGE PUMP	YES
AXLE BEARING EXTENSIONS	Standard
ENTRY STEP	OPT
SEATING TYPE	Standard
BEDLINER	NO
OPERATING CONDITIONS	-40°C - +40°C

### INSTRUMENTATION

Analog Digital Gauge Cluster, Speedometer, Odometer, Voltmeter, Hour Meter, Tachometer, Low Oil Pressure, Parking Brake Reminder Lights and Check Engine Light

### COLORS

AVAILABLE COLORS	Industrial Yellow
------------------	-------------------

\*OPT are Dealer Installed items



# 2018 ARGO XTV



# Conquest 8x8 XT-L

ENGINE	
DISPLACEMENT	747cc
TYPE	4-cycle OHV
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Liquid
ALTERNATOR	60 AMP
HP	30

STEERING/WHEELS/TIRES	
STEERING	Multi Position, one piece handlebar
RIMS	Steel off-set
TIRES	ARGO AT189 25 X 12-9
GROUND PRESSURE	2.5 psi (17.2 kPa)
GROUND CLEARANCE - TIRES	9 in (230 mm)
GROUND CLEARANCE - TRACKS	10 in (255 mm)
CONTROLS	Right hand twist grip throttle

POWERTRAIN	
TRANSMISSION	Admiral
TRANSMISSION OPTION	STD
FINAL DRIVE	RC60 chains
DRIVE BELT	Standard
GEAR SELECTION	L/H/N/R
CLUTCH	Belt-driven
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	OPT

DIMENSIONS/WEIGHT/CAPACITY	
LENGTH	125 in (3106 mm)
WIDTH	65 in (1651 mm)
HEIGHT	79in (2007 mm)
LOAD CAPACITY - LAND	1,000 lb. (454 kg)
LOAD CAPACITY - WATER	NA

DIMENSIONS/WEIGHT/CAPACITY - continued	
LOAD CAPACITY - REAR	NA
TOWING CAPACITY	2,000 lb. (907 kg)
DRY WEIGHT	2,100 lb. (953 kg)
FUEL CAPACITY	7.1 gal (27 ltr)
SEAT CAPACITY	2 Land / NA
FRONT RACK	NO
SPEED ON LAND	17 mph (27 km)
SPEED ON WATER	3 mph (5 km)

FEATURES	
BRUSHGUARD	YES
WINCH	4,500 lb. ProVantage
SKID PLATE	YES
BILGE PUMP	YES
AXLE BEARING EXTENSIONS	Standard
ENTRY STEP	OPT
SEATING TYPE	Standard
BEDLINER	NO
OPERATING CONDITIONS	-40°C - +40°C

**INSTRUMENTATION**  
Analog Digital Gauge Cluster, Speedometer, Odometer, Voltmeter, Hour Meter, Tachometer, Low Oil Pressure, Parking Brake Reminder Lights and Check Engine Light

COLORS	
AVAILABLE COLORS	Industrial Yellow

\*OPT are Dealer Installed items

